



Features:

- -55°C to 125°C operating temperature range
- EIA sizes 0402, 0603, 0805, 1206, 1210 and 1812
- Capacitance offering from 0.1 pF to 0.1 uF
- RoHS compliant, REACH compliant, lead free and halogen free



Construction



- 1 - Ceramic layers (dielectric)
- 2 - Inner electrodes
- 3 - Base termination
- 4 - Nickel plating layer
- 5 - Tin plating layer

Electrical Specifications

Type/Code	Dielectric Code	Standard Tolerance		Capacitance Range	
		Code	Description	50V	100V
CML0402	C0G	C	± 0.25 pF	0.1 pF - 8.2 pF	-
		J	± 5%	10 pF - 1000 pF	-
CML0603	C0G	C	± 0.25 pF	0.1 pF - 6.8 pF	0.5 pF - 8.2 pF
		J	± 5%	10 pF - 6800 pF	10 pF - 1000 pF
CML0805	C0G	C	± 0.25 pF	0.3 pF - 6.8 pF	0.5 pF - 8.2 pF
		J	± 5%	10 pF - 0.022 uF	10 pF - 3300 pF
CML1206	C0G	C	± 0.25 pF	0.3 pF - 8.2 pF	0.5 pF - 8.2 pF
		J	± 5%	10 pF - 3300 pF	10 pF - 3300 pF
				3900 pF - 4700 pF	-
CML1210	C0G	C	± 0.25 pF	-	1 pF - 8.2 pF
		J	± 5%	10 pF - 0.1 uF	10 pF - 6800 pF
CML1812	C0G	C	± 0.25 pF	-	3 pF - 8.2 pF
		J	± 5%	10 pF - 0.1 uF	10 pF - 0.01 uF

Note: Capacitance values < 10 pF: B = ± 0.1 pF may be available
Capacitance values ≥ 10 pF: G = ± 2% may be available

How to Order


C	M	L	0	4	0	2	C	0	G	1	0	0	J	T	5	0	V
Product Series		Size	Dielectric		Capacitance Range		Tolerance (*)		Packaging			Max Working Voltage					
Code	Description	Code	Code	0.1pF to 0.10uF (E12)		Code	Description	Code	Description	Size and Quantity		50V 100V					
CML	Multilayer Ceramic	0402 0603 0805 1206 1210 1812	C0G	EIA Code	Capacitance	B	± 0.1 pF	T	7" Paper Reel 7" Plastic Tape	Refer to Packaging Specifications							
				0R1	0.1 pF	C	± 0.25 pF										
				100	10 pF	G	± 2%										
				101	100 pF	J	± 5%										
				102	1000 pF												
				103	0.01 uF												
				104	0.1 uF												

(*) Other tolerances may be available. Contact Stackpole.


Capacitance and Voltage Available															
Dielectric		C0G													
EIA Code	Size	0402			0603			0805		1206		1210		1812	
	VDCW	50V	50V	100V	50V	50V	100V	50V	100V	50V	100V	50V	100V	50V	100V
0R1	0.1 pF														
0R2	0.2 pF														
0R3	0.3 pF														
0R4	0.4 pF														
0R5	0.5 pF														
0R6	0.6 pF														
0R7	0.7 pF														
0R8	0.8 pF														
0R9	0.9 pF														
1R0	1 pF														
1R2	1.2 pF														
1R5	1.5 pF														
1R8	1.8 pF														
2R0	2 pF														
2R2	2.2 pF														
2R7	2.7 pF														
3R0	3 pF														
3R3	3.3 pF														
3R9	3.9 pF														
4R7	4.7 pF														
5R0	5 pF														
5R6	5.6 pF														
6R8	6.8 pF														
8R2	8.2 pF														
100	10 pF														
120	12 pF														
150	15 pF														
180	18 pF														
220	22 pF														
270	27 pF														
330	33 pF														
390	39 pF														
470	47 pF														
560	56 pF														
680	68 pF														
820	82 pF														
101	100 pF														
121	120 pF														
151	150 pF														
181	180 pF														
221	220 pF														
271	270 pF														
331	330 pF														
391	390 pF														
471	470 pF														
561	560 pF														
681	680 pF														
751	750 pF														
821	820 pF														
102	1000 pF														
122	1200 pF														
152	1500 pF														
182	1800 pF														
222	2200 pF														
272	2700 pF														
332	3300 pF														
392	3900 pF														
472	4700 pF														
562	5600 pF														
682	6800 pF														
822	8200 pF														
103	0.01 uF														

Capacitance and Voltage Available (cont.)															
Dielectric		C0G													
EIA Code	Size	0402			0603			0805		1206		1210		1812	
	VDCW	50V	50V	100V	50V	50V	100V	50V	100V	50V	100V	50V	100V	50V	100V
123	0.012 uF														
153	0.015 uF														
183	0.018 uF														
223	0.022 uF														
273	0.027 uF														
333	0.033 uF														
473	0.047 uF														
563	0.056 uF														
683	0.068 uF														
823	0.082 uF														
104	0.1 uF														

Mechanical Specifications and Packaging Specifications



Type/Code	Voltage	Capacitance Value	L	W	H	a	Unit	Packaging (7" Reel) Qty.	
								Paper Tape	Plastic Tape
CML0402C0G	50V	0.1 pF - 1000 pF	0.039 ± 0.008 1.00 ± 0.20	0.020 ± 0.008 0.50 ± 0.20	0.020 ± 0.002 0.50 ± 0.05	0.010 ± 0.004 0.25 ± 0.10	inches mm	10000	-
CML0603C0G	50V - 100V	0.1 pF - 6800 pF	0.063 ± 0.008 1.60 ± 0.20	0.031 ± 0.008 0.80 ± 0.20	0.031 ± 0.004 0.80 ± 0.10	0.012 ± 0.004 0.30 ± 0.10	inches mm	4000	-
CML0805C0G	50V	0.3 pF - 1500 pF 4700 pF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.028 ± 0.002 0.70 ± 0.05	0.020 ± 0.008 0.50 ± 0.20	inches mm	4000	-
		1800 pF - 3900 pF	0.079 ± 0.008	0.049 ± 0.008	0.031 ± 0.004	0.020 ± 0.008	inches	4000	-
		5600 pF - 8200 pF	2.00 ± 0.20	1.25 ± 0.20	0.80 ± 0.09	0.50 ± 0.20	mm	-	2000
		0.01 uF - 0.022 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.047 ± 0.004 1.20 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	2000
	100V	0.5 pF - 3300 pF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.031 ± 0.004 0.80 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	4000	-
CML1206C0G	50V	0.3 pF - 8200 pF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.028 ± 0.002 0.70 ± 0.05	0.024 ± 0.012 0.60 ± 0.30	inches mm	4000	-
		0.01 uF - 0.1 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.063 ± 0.004 1.60 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
	100V	0.5 pF - 3300 pF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.031 ± 0.004 0.80 ± 0.09	0.024 ± 0.012 0.60 ± 0.30	inches mm	4000	-
CML1210C0G	50V	10 pF - 0.1 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	3000
	100V	1 pF - 6800 pF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
CML1812C0G	50V	10 pF - 0.1 uF	0.177 ± 0.016 4.50 ± 0.40	0.126 ± 0.012 3.20 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	1000
	100V	3 pF - 0.01 uF	0.177 ± 0.016 4.50 ± 0.40	0.126 ± 0.012 3.20 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	1000

Environmental Characteristics			
Test	Test Specification		Test Condition
Capacitance	Should be within the specified tolerance.		C0G: (Class I) Cap ≤ 1000 pF 1.0 ± 0.2 Vrms, 1 MHz ± 10% Cap > 1000 pF 1.0 ± 0.2 Vrms, 1 KHz ± 10%
Dissipation Factor (DF)	C0G (Class I)	DF	Capacitance
		≤ 0.56%	Cr < 5 pF
		1.5 [(150 / Cr) + 7] × 10 ⁻⁴	5 pF ≤ Cr < 50 pF
		≤ 0.15%	50 pF ≤ Cr ≤ 1000 pF
		≤ 0.15%	> 1000 pF
Insulation Resistance	C0G (Class I)	C ≤ 10 nF, Ri ≥ 50000 MΩ C > 10 nF, Ri*CR ≥ 500 S	Measuring Voltage: Rated Voltage (Max 500V) Duration: 60 ± 5 seconds Test Humidity: ≤ 75% Test Temperature: 25°C ± 5°C Test Current: ≤ 50 mA
			Measuring voltage: Class I: 300% rated voltage Duration: 1 ~ 5 seconds Charge/Discharge Current: 50 mA max.
Dielectric Withstanding Voltage	No breakdown or damage.		Preheating Conditions: 80°C to 120°C, 10 ~ 30 seconds Solder Temperature: 235°C ± 5% (Sn/Pb: 63/37) Duration: 2 ± 0.5 seconds Solder Temperature: 245°C ± 5°C (Lead-free) Duration: 2 ± 0.5 seconds
Solderability	At least 95% of the terminal electrode is covered by new solder. Visual appearance: No visible damage.		Preheating Conditions: 100°C to 200°C; 10 ± 2 minutes Solder Temperature: 265°C ± 5°C Duration: 10 ± 1 seconds Clean the capacitor with solvent and examine it with a 10X (min.) microscope. Recovery Time: 24 ± 2 hours Recovery Condition: Room temperature.
			Test Board: Al2O3 or PCB Warp: 1 mm Speed: 0.5 mm/second The measurement should be made with the board in the bending position.
			
			Unit: mm
Resistance to Soldering Heat	Item	C0G	Applied Force: 5 N Duration: 10 ± 1 seconds
	Δ C/C	≤ ± 0.5% or ± 0.5 pF whichever is larger	Preheating Conditions: up-category Temperature: 1 hour Recovery Time: 24 ± 1 hours Initial Measurement
	DF	Same to initial value	Cycling times: 5 times, 1 cycle, 4 steps:
	IR	Same to initial value	Step
Appearance: No visible damage. At least 95% of the terminal electrode is covered by new solder.			Temp. (°C)
Resistance to Flexure of Substrate (Bending Strength)	Appearance: No visible damage. Δ C/C: ≤ ± 10%		Time (min.)
			1
			2
			3
Termination Adhesion	No visible damage		4
Temperature Cycle	C0G: Δ C/C: ≤ ± 1% or ± 1 pF, whichever is larger		Recovery time after test: 24 ± 2 hours

Environmental Characteristics (cont.)		
Test	Test Specification	Test Condition
Moisture Resistance	C0G: $\Delta C/C: \leq \pm 2\%$ or ± 1 pF, whichever is larger DF: Not more than twice of initial value. IR: C0G: $R_i \geq 2500$ M Ω or $R_i \cdot CR \geq 25$ S whichever is smaller Appearance: No visible damage	Temperature: $40^\circ\text{C} \pm 2^\circ\text{C}$ Humidity: 90 ~ 95% R.H. Duration: 500 hours Recovery Conditions: Room temperature Recovery Time: 24 hours (Class I)
Life Test	C0G: $\Delta C/C: \leq \pm 2\%$ or ± 1 pF, whichever is larger DF: Not more than twice of initial value. IR: C0G: $R_i \geq 4000$ M Ω or $R_i \cdot CR \geq 40$ S whichever is smaller Appearance: No visible damage	Low-voltage (< 100V) Applied Voltage: 1.5 x rated voltage Duration: 1000 hours Temperature: 125°C (C0G) Charge/Discharge Current: 50 mA max. Recovery Conditions: Room temperature Recovery Time: 24 hours (Class I)
Middle and High Voltage Life Test	C0G: $\Delta C/C: \leq \pm 2\%$ or ± 1 pF, whichever is larger DF: Not more than twice of initial value. IR: C0G: $R_i \geq 4000$ M Ω or $R_i \cdot CR \geq 40$ S whichever is smaller Appearance: No visible damage	Applied voltage: $100\text{V} \leq$ rated voltage < 500V: 2 multiple $500\text{V} \leq$ rated voltage $\leq 1000\text{V}$: 1.5 multiple > 1000V rated voltage: 1.2 multiple Duration: 1000 hours Charge/Discharge Current: 50 mA max. Temperature: 125°C (C0G) Recovery Conditions: Room temperature Recovery Time: 24 hours (Class I)


Reel Specifications								
Type/Code	A	B	C	D	E	F	G	Unit
CML_C0G (all sizes)	7.008 ± 0.079 178.00 ± 2.00	0.118 3.00	0.512 ± 0.020 13.00 ± 0.50	0.827 ± 0.031 21.00 ± 0.80	1.969 or more 50.00 or more	0.394 ± 0.059 10.00 ± 1.50	0.472 max 12.00 max	inches mm

Paper Tape Specifications						
Type/Code	A ₀	B ₀	T	W	P ₀	Unit
CML0402C0G	0.026 ± 0.004 0.65 ± 0.10	0.045 ± 0.004 1.15 ± 0.10	0.031 below 0.80 below	0.315 ± 0.004 8.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	inches mm
CML0603C0G	0.043 ± 0.004 1.10 ± 0.10	0.075 ± 0.004 1.90 ± 0.10	0.043 max 1.10 max	0.315 ± 0.004 8.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	inches mm
CML0805C0G	0.057 ± 0.006 1.45 ± 0.15	0.091 ± 0.006 2.30 ± 0.15	0.043 max 1.10 max	0.315 ± 0.006 8.00 ± 0.15	0.157 ± 0.004 4.00 ± 0.10	inches mm
CML1206C0G	0.071 ± 0.008 1.80 ± 0.20	0.134 ± 0.008 3.40 ± 0.20	0.043 max 1.10 max	0.315 ± 0.008 8.00 ± 0.20	0.157 ± 0.004 4.00 ± 0.10	inches mm

Paper Tape Specifications (cont.)

Type/Code	P ₁	P ₂	D ₀	E	F	Unit
CML0402C0G	0.079 ± 0.002 2.00 ± 0.05	0.079 ± 0.002 2.00 ± 0.05	0.059-0/+0.004 1.5-0/+0.10	0.069 ± 0.002 1.75 ± 0.05	0.138 ± 0.002 3.50 ± 0.05	inches mm
CML0603C0G	0.079 ± 0.004 2.00 ± 0.10	0.157 ± 0.002 4.00 ± 0.05	0.059-0/+0.004 1.5-0/+0.10	0.069 ± 0.002 1.75 ± 0.05	0.138 ± 0.002 3.50 ± 0.05	inches mm
CML0805C0G	0.079 ± 0.004 2.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	0.059-0/+0.004 1.5-0/+0.10	0.069 ± 0.002 1.75 ± 0.05	0.138 ± 0.002 3.50 ± 0.05	inches mm
CML1206C0G	0.079 ± 0.004 2.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	0.059-0/+0.004 1.5-0/+0.10	0.069 ± 0.004 1.75 ± 0.10	0.138 ± 0.002 3.50 ± 0.05	inches mm


Plastic Tape Specifications



Type/Code	A	B	C	D	E	Unit
CML0805C0G	0.061 ± 0.008 1.55 ± 0.20	0.093 ± 0.008 2.35 ± 0.20	0.315 ± 0.008 8.00 ± 0.20	0.138 ± 0.002 3.50 ± 0.05	0.069 ± 0.004 1.75 ± 0.10	inches mm
CML1206C0G	0.077 ± 0.008 1.95 ± 0.20	0.142 ± 0.008 3.60 ± 0.20	0.315 ± 0.008 8.00 ± 0.10	0.138 ± 0.002 3.50 ± 0.05	0.069 ± 0.004 1.75 ± 0.10	inches mm
CML1210C0G	0.106 ± 0.004 2.70 ± 0.10	0.135 ± 0.004 3.42 ± 0.10	0.315 ± 0.004 8.00 ± 0.10	0.138 ± 0.002 3.50 ± 0.05	0.069 ± 0.004 1.75 ± 0.10	inches mm
CML1812C0G	0.144 ± 0.004 3.66 ± 0.10	0.195 ± 0.004 4.95 ± 0.10	0.472 ± 0.004 12.00 ± 0.10	0.217 ± 0.002 5.50 ± 0.05	0.069 ± 0.004 1.75 ± 0.10	inches mm
Type/Code	F	G	H	J	T	Unit
CML0805C0G	0.157 ± 0.004 4.00 ± 0.10	0.079 ± 0.004 2.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	0.059-0/+0.004 1.5-0/+0.10	0.059 max 1.50 max	inches mm
CML1206C0G	0.157 ± 0.004 4.00 ± 0.10	0.079 ± 0.004 2.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	0.059-0/+0.004 1.5-0/+0.10	0.073 max 1.85 max	inches mm
CML1210C0G	0.157 ± 0.004 4.00 ± 0.10	0.079 ± 0.002 2.00 ± 0.05	0.157 ± 0.004 4.00 ± 0.10	0.059-0/+0.004 1.5-0/+0.10	0.126 max 3.20 max	inches mm
CML1812C0G	0.315 ± 0.004 8.00 ± 0.10	0.079 ± 0.002 2.00 ± 0.05	0.157 ± 0.004 4.00 ± 0.10	0.059-0/+0.004 1.5-0/+0.10	0.157 max 4.00 max	inches mm

Recommended Solder Pad for Wave Soldering

Type	0603	0805	1206	1210	Unit
Length (L)	0.063	0.079	0.126	0.126	inches
	1.60	2.00	3.20	3.20	mm
Width (W)	0.031	0.049	0.063	0.098	inches
	0.80	1.25	1.60	2.50	mm
a	0.031 ~ 0.039	0.039 ~ 0.055	0.071 ~ 0.098	0.071 ~ 0.098	inches
	0.80 ~ 1.00	1.00 ~ 1.40	1.80 ~ 2.50	1.80 ~ 2.50	mm
b	0.020 ~ 0.031	0.031 ~ 0.059	0.031 ~ 0.067	0.031 ~ 0.067	inches
	0.50 ~ 0.80	0.80 ~ 1.50	0.80 ~ 1.70	0.80 ~ 1.70	mm
c	0.024 ~ 0.031	0.035 ~ 0.047	0.047 ~ 0.063	0.071 ~ 0.098	inches
	0.60 ~ 0.80	0.90 ~ 1.20	1.20 ~ 1.60	1.80 ~ 2.50	mm



NOTE: Solder pad information is for reference only.

Recommended Solder Pad for Reflow Soldering

Type	0402	0603	0805	1206	1210	1812	Unit
Length (L)	0.043	0.063	0.079	0.126	0.126	0.177	inches
	1.10	1.60	2.00	3.20	3.20	4.50	mm
Width (W)	0.020	0.031	0.049	0.063	0.098	0.126	inches
	0.50	0.80	1.25	1.60	2.50	3.20	mm
a	0.018 ~ 0.022	0.024 ~ 0.031	0.031 ~ 0.047	0.071 ~ 0.098	0.071 ~ 0.098	0.098 ~ 0.138	inches
	0.45 ~ 0.55	0.60 ~ 0.80	0.80 ~ 1.20	1.80 ~ 2.50	1.80 ~ 2.50	2.50 ~ 3.50	mm
b	0.016 ~ 0.020	0.024 ~ 0.031	0.024 ~ 0.047	0.024 ~ 0.059	0.024 ~ 0.059	0.039 ~ 0.071	inches
	0.40 ~ 0.50	0.60 ~ 0.80	0.60 ~ 1.20	0.60 ~ 1.50	0.60 ~ 1.50	1.00 ~ 1.80	mm
c	0.018 ~ 0.022	0.024 ~ 0.031	0.035 ~ 0.063	0.047 ~ 0.079	0.071 ~ 0.126	0.091 ~ 0.138	inches
	0.45 ~ 0.55	0.60 ~ 0.80	0.90 ~ 1.60	1.20 ~ 2.00	1.80 ~ 3.20	2.30 ~ 3.50	mm

NOTE: Solder pad information is for reference only.

RoHS Compliance

Stackpole Electronics has joined the worldwide effort to reduce the amount of lead in electronic components and to meet the various regulatory requirements now prevalent, such as the European Union’s directive regarding “Restrictions on Hazardous Substances” (RoHS 3). As part of this ongoing program, we periodically update this document with the status regarding the availability of our compliant components. All our standard part numbers are compliant to EU Directive 2011/65/EU of the European Parliament as amended by Directive (EU) 2015/863/EU as regards the list of restricted substances.

RoHS Compliance Status

Standard Product Series	Description	Package / Termination Type	Standard Series RoHS Compliant	Lead-Free Termination Composition	Lead-Free Mfg. Effective Date (Std Product Series)	Lead-Free Effective Date Code (YY/WW)
CML	Multilayer Ceramic Chip Capacitor	SMD	YES	100% Matte Sn over Ni	Always	Always

“Conflict Metals” Commitment

We at Stackpole Electronics, Inc. are joined with our industry in opposing the use of metals mined in the “conflict region” of the eastern Democratic Republic of the Congo (DRC) in our products. Recognizing that the supply chain for metals used in the electronics industry is very complex, we work closely with our own suppliers to verify to the extent possible that the materials and products we supply do not contain metals sourced from this conflict region. As such, we are in compliance with the requirements of Dodd-Frank Act regarding Conflict Minerals.

Compliance to “REACH”


We certify that all passive components supplied by Stackpole Electronics, Inc. are SVHC (Substances of Very High Concern) free and compliant with the requirements of EU Directive 1907/2006/EC, “The Registration, Evaluation, Authorization and Restriction of Chemicals”, otherwise referred to as REACH. Contact us for complete list of REACH Substance Candidate List.

Environmental Policy


It is the policy of Stackpole Electronics, Inc. to protect the environment in all localities in which we operate. We continually strive to improve our effect on the environment. We observe all applicable laws and regulations regarding the protection of our environment and all requests related to the environment to which we have agreed. We are committed to the prevention of all forms of pollution.

Features:

- 55°C to 85°C operating temperature range
- EIA sizes 0402, 0603, 0805, 1206, 1210 and 1812
- Capacitance offering from 0.047 uF to 100 uF
- RoHS compliant, REACH compliant, lead free and halogen free



Construction



- 1 - Ceramic layers (dielectric)
- 2 - Inner electrodes
- 3 - Base termination
- 4 - Nickel plating layer
- 5 - Tin plating layer

Electrical Specifications

Type / Code	Dielectric Code	Standard Code	Tolerance Description	Capacitance Range			
				10V	16V	25V	50V
CML0402	X5R	K	± 10%	120 pF - 0.039 uF			
				0.047 uF - 0.1 uF		-	
				0.12 uF - 0.47 uF		-	
CML0603	X5R	K	± 10%	0.47 uF - 1 uF			
				1.2 uF - 2.2 uF		-	
CML0805	X5R	K	± 10%	150 pF - 0.39 uF			
				0.47 uF - 2.2 uF		-	
CML1206	X5R	K	± 10%	150 pF - 4.7 uF			
				10 uF	-		
CML1210	X5R	K	± 10%	4.7 uF - 22 uF			
				33 uF - 47 uF		-	
				68 uF - 100 uF		-	
CML1812	X5R	K	± 10%	4.7 uF - 6.8 uF			
				10 uF		-	
				15 uF - 22 uF		-	
				33 uF - 47 uF		-	


Note: J = ± 5% tolerance may be available

How to Order

C	M	L	0	4	0	2	X	5	R	1	0	4	K	T	5	0	V
Product Series		Size	Dielectric	Capacitance Range		Tolerance (*)		Packaging			Max Working Voltage						
Code	Description	Code	Code	EIA Code	Capacitance	Code	Description	Code	Description	Size	Quantity						
CML	Multilayer Ceramic	0402	X5R	473	0.047 uF	J	± 5%	T	7" Paper Reel	Refer to Packaging Specifications		10V					
		0603		104	0.1 uF	K	± 10%		7" Plastic Tape			16V					
		0805		105	1 uF							25V					
		1206		106	10 uF							50V					
		1210		107	100 uF												
		1812															

(*) Other tolerances may be available. Contact Stackpole.

Capacitance and Voltage Available																								
Dielectric		X5R																						
EIA	Size	0402				0603				0805			1206				1210			1812				
Code	VDCW	10V	16V	25V	50V	10V	16V	25V	50V	10V	16V	25V	10V	16V	25V	50V	10V	16V	25V	10V	16V	25V		
473	0.047 uF																							
563	0.056 uF																							
683	0.068 uF																							
823	0.082 uF																							
104	0.1 uF																							
154	0.15 uF																							
224	0.22 uF																							
334	0.33 uF																							
474	0.47 uF																							
684	0.68 uF																							
105	1 uF																							
155	1.5 uF																							
225	2.2 uF																							
335	3.3 uF																							
475	4.7 uF																							
685	6.8 uF																							
106	10 uF																							
156	15 uF																							
226	22 uF																							
336	33 uF																							
476	47 uF																							
686	68 uF																							
107	100 uF																							


Mechanical Specifications and Packaging Specifications									
									
Type / Code	Voltage	Capacitance Range	L	W	H	a	Unit	Packaging (7" Reel) Qty.	
								Paper Tape	Plastic Tape
CML0402X5R	10V - 50V	0.1 uF - 4.7 uF	0.039 ± 0.008 1.00 ± 0.20	0.020 ± 0.008 0.50 ± 0.20	0.020 ± 0.002 0.50 ± 0.05	0.010 ± 0.004 0.25 ± 0.10	inches mm	10000	-
CML0603X5R	10V - 50V	0.47 uF - 10 uF	0.063 ± 0.008 1.60 ± 0.20	0.031 ± 0.008 0.80 ± 0.20	0.031 ± 0.004 0.80 ± 0.10	0.012 ± 0.004 0.30 ± 0.10	inches mm	4000	-
CML0805X5R	10V - 16V	1 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.039 ± 0.004 1.00 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	3000
		1.5 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.047 ± 0.004 1.20 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	3000
		2.2 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.031 ± 0.004 0.80 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	4000	-
	25V	3.3 uF - 22 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.047 ± 0.004 1.20 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	2000
		1 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.039 ± 0.004 1.00 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	3000
		1.5 uF - 2.2 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.047 ± 0.004 1.20 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	3000
3.3 uF - 10 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.047 ± 0.004 1.20 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	2000		

Mechanical Specifications and Packaging Specifications (cont.)


Type / Code	Voltage	Capacitance Range	L	W	H	a	Unit	Packaging (7" Reel) Qty.	
								Paper Tape	Plastic Tape
CML1206X5R	10V	2.2 uF - 3.3 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	3000
		4.7 uF - 22 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.063 ± 0.004 1.60 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		47 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.071 ± 0.004 1.80 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
	16V - 25V	2.2 uF - 3.3 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	3000
		4.7 uF - 22 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.063 ± 0.004 1.60 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
	50V	2.2 uF - 3.3 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	3000
4.7 uF - 10 uF		0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.063 ± 0.004 1.60 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000	
CML1210X5R	10V	4.7 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		6.8 uF - 10 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.071 ± 0.004 1.80 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		15 uF - 100 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.098 ± 0.010 2.50 ± 0.25	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	500
	16V	4.7 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		6.8 uF - 10 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.071 ± 0.004 1.80 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		15 uF - 47 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.098 ± 0.010 2.50 ± 0.25	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	500
	25V	4.7 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		6.8 uF - 10 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.071 ± 0.004 1.80 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		15 uF - 22 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.098 ± 0.010 2.50 ± 0.25	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	500
CML1812X5R	10V - 25V	4.7 uF - 47 uF	0.177 ± 0.016 4.50 ± 0.40	0.126 ± 0.012 3.20 ± 0.30	0.071 ± 0.004 1.80 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	1000

Environmental Characteristics

Test	Test Specification				Test Condition		
Capacitance	Should be within the specified tolerance.				X5R: (Class II) Cap ≤ 10 uF 1.0 ± 0.2 Vrms, 1 KHz ± 10% Cap > 10 uF 0.5 ± 0.1 Vrms, 120 Hz ± 10%		
Dissipation Factor (DF)	X5R (Class II)	X5R (≥ 0402)	≥ 50V	25V	16V	10V	
			≤ 2.5%	≤ 3.5% (C < 0.47 uF) ≤ 10.0% (C ≥ 0.47 uF)	≤ 5% (C < 0.15 uF) ≤ 10.0% (C ≥ 0.15 uF)		
Insulation Resistance	X5R (Class II)	C ≤ 25 nF, Ri ≥ 10,000 MΩ C > 25 nF, Ri*CR > 100 S				Measuring Voltage: Rated Voltage (Max 500V) Duration: 60 ± 5 seconds Test Humidity: ≤ 75% Test Temperature: 25°C ± 5°C Test Current: ≤ 50 mA	
Dielectric Withstanding Voltage	No breakdown or damage.				Measuring voltage: Class II: 250% rated voltage Duration: 1 ~ 5 seconds Charge/Discharge Current: 50 mA max.		


Environmental Characteristics (cont.)																	
Test	Test Specification	Test Condition															
Solderability	At least 95% of the terminal electrode is covered by new solder. Visual appearance: No visible damage.	Preheating Conditions: 80°C to 120°C, 10 ~ 30 seconds															
		Solder Temperature: 235°C ± 5% (Sn/Pb: 63/37) Duration: 2 ± 0.5 seconds															
Resistance to Soldering Heat	Appearance: No visible damage. At least 95% of the terminal electrode is covered by new solder.	Solder Temperature: 245°C ± 5°C (Lead-free) Duration: 2 ± 0.5 seconds															
		Preheating Conditions: 100°C to 200°C; 10 ± 2 minutes Solder Temperature: 265°C ± 5 °C Duration: 10 ± 1 seconds															
		Clean the capacitor with solvent and examine it with a 10X (min.) microscope.															
		Recovery Time: 24 ± 2 hours															
		Recovery Condition: Room temperature.															
Resistance to Flexure of Substrate (Bending Strength)	Appearance: No visible damage. $\Delta C/C: \leq \pm 10\%$	Test Board: Al ₂ O ₃ or PCB Warp: 1 mm Speed: 0.5 mm / second The measurement should be made with the board in the bending position. Unit: mm															
																	
Termination Adhesion	No visible damage	Applied Force: 5 N Duration: 10 ± 1 seconds															
Temperature Cycle	X5R: $\Delta C/C: \leq \pm 10\%$	Preheating Conditions: up-category temperature 1 hour Recovery Time: 24 ± 1 hours Initial Measurement															
		Cycling times: 5 times, 1 cycle, 4 steps:															
		<table border="1"> <thead> <tr> <th>Step</th> <th>Temp. (°C)</th> <th>Time (min.)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Low-category temp. X5R: -55°C</td> <td>30 ± 3</td> </tr> <tr> <td>2</td> <td>Normal temp. (+20°C)</td> <td>2 - 3</td> </tr> <tr> <td>3</td> <td>Up-category temp. X5R: +85°C</td> <td>30 ± 3</td> </tr> <tr> <td>4</td> <td>Normal temp. (+20°C)</td> <td>2 - 3</td> </tr> </tbody> </table>	Step	Temp. (°C)	Time (min.)	1	Low-category temp. X5R: -55°C	30 ± 3	2	Normal temp. (+20°C)	2 - 3	3	Up-category temp. X5R: +85°C	30 ± 3	4	Normal temp. (+20°C)	2 - 3
		Step	Temp. (°C)	Time (min.)													
		1	Low-category temp. X5R: -55°C	30 ± 3													
2	Normal temp. (+20°C)	2 - 3															
3	Up-category temp. X5R: +85°C	30 ± 3															
4	Normal temp. (+20°C)	2 - 3															
Recovery time after test: 24 ± 2 hours																	
Moisture Resistance	X5R: $\Delta C/C: \leq \pm 10\%$ DF: Not more than twice of initial value. IR: X5R: $R_i \geq 1000 M\Omega$ or $R_i \cdot CR \geq 25 S$ whichever is smaller Appearance: No visible damage	Temperature: 40°C ± 2°C Humidity: 90 ~ 95% R.H. Duration: 500 hours Recovery Conditions: Room temperature Recovery Time: 48 hours (Class II)															
Life Test	X5R: $\Delta C/C: \leq \pm 20\%$ DF: Not more than twice of initial value. IR: X5R: $R_i \geq 2000 M\Omega$ or $R_i \cdot CR \geq 50 S$ whichever is smaller Appearance: No visible damage	Low-voltage (< 100V) Applied Voltage: 1.5 x rated voltage Duration: 1000 hours Temperature: 85°C (X5R) Charge/Discharge Current: 50 mA max. Recovery Conditions: Room temperature Recovery Time: 48 hours (Class II)															

Reel Specifications




Type/Code	A	B	C	D	E	F	G	Unit
CML_X5R (all sizes)	7.008 ± 0.079 178.00 ± 2.00	0.118 3.00	0.512 ± 0.020 13.00 ± 0.50	0.827 ± 0.031 21.00 ± 0.80	1.969 or more 50.00 or more	0.394 ± 0.059 10.00 ± 1.50	0.472 max 12.00 max	inches mm

Paper Tape Specifications



Type/Code	A0	B0	T	W	P0	Unit
CML0402X5R	0.026 ± 0.004 0.65 ± 0.10	0.045 ± 0.004 1.15 ± 0.10	0.031 below 0.80 below	0.315 ± 0.004 8.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	inches mm
CML0603X5R	0.043 ± 0.004 1.10 ± 0.10	0.075 ± 0.004 1.90 ± 0.10	0.043 max 1.10 max	0.315 ± 0.004 8.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	inches mm
CML0805X5R	0.057 ± 0.006 1.45 ± 0.15	0.091 ± 0.006 2.30 ± 0.15	0.043 max 1.10 max	0.315 ± 0.006 8.00 ± 0.15	0.157 ± 0.004 4.00 ± 0.10	inches mm
CML1206X5R	0.071 ± 0.008 1.80 ± 0.20	0.134 ± 0.008 3.40 ± 0.20	0.043 max 1.10 max	0.315 ± 0.008 8.00 ± 0.20	0.157 ± 0.004 4.00 ± 0.10	inches mm
Type/Code	P1	P2	D0	E	F	Unit
CML0402X5R	0.079 ± 0.002 2.00 ± 0.05	0.079 ± 0.002 2.00 ± 0.05	0.059-0/+0.004 1.5-0/+0.10	0.069 ± 0.002 1.75 ± 0.05	0.138 ± 0.002 3.50 ± 0.05	inches mm
CML0603X5R	0.079 ± 0.004 2.00 ± 0.10	0.157 ± 0.002 4.00 ± 0.05	0.059-0/+0.004 1.5-0/+0.10	0.069 ± 0.002 1.75 ± 0.05	0.138 ± 0.002 3.50 ± 0.05	inches mm
CML0805X5R	0.079 ± 0.004 2.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	0.059-0/+0.004 1.5-0/+0.10	0.069 ± 0.002 1.75 ± 0.05	0.138 ± 0.002 3.50 ± 0.05	inches mm
CML1206X5R	0.079 ± 0.004 2.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	0.059-0/+0.004 1.5-0/+0.10	0.069 ± 0.004 1.75 ± 0.10	0.138 ± 0.002 3.50 ± 0.05	inches mm


Plastic Tape Specifications



Type/Code	A	B	C	D	E	Unit
CML0805X5R	0.061 ± 0.008 1.55 ± 0.20	0.093 ± 0.008 2.35 ± 0.20	0.315 ± 0.008 8.00 ± 0.20	0.138 ± 0.002 3.50 ± 0.05	0.069 ± 0.004 1.75 ± 0.10	inches mm
CML1206X5R	0.077 ± 0.008 1.95 ± 0.20	0.142 ± 0.008 3.60 ± 0.20	0.315 ± 0.008 8.00 ± 0.20	0.138 ± 0.002 3.50 ± 0.05	0.069 ± 0.004 1.75 ± 0.10	inches mm
CML1210X5R	0.106 ± 0.004 2.70 ± 0.10	0.135 ± 0.004 3.42 ± 0.10	0.315 ± 0.004 8.00 ± 0.10	0.138 ± 0.002 3.50 ± 0.05	0.069 ± 0.004 1.75 ± 0.10	inches mm
CML1812X5R	0.144 ± 0.004 3.66 ± 0.10	0.195 ± 0.004 4.95 ± 0.10	0.472 ± 0.004 12.00 ± 0.10	0.217 ± 0.002 5.50 ± 0.05	0.069 ± 0.004 1.75 ± 0.10	inches mm
Type/Code	F	G	H	J	T	Unit
CML0805X5R	0.157 ± 0.004 4.00 ± 0.10	0.079 ± 0.004 2.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	0.059-0/+0.004 1.5-0/+0.10	0.059 max 1.50 max	inches mm
CML1206X5R	0.157 ± 0.004 4.00 ± 0.10	0.079 ± 0.004 2.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	0.059-0/+0.004 1.5-0/+0.10	0.073 max 1.85 max	inches mm
CML1210X5R	0.157 ± 0.004 4.00 ± 0.10	0.079 ± 0.002 2.00 ± 0.05	0.157 ± 0.004 4.00 ± 0.10	0.059-0/+0.004 1.5-0/+0.10	0.126 max 3.20 max	inches mm
CML1812X5R	0.315 ± 0.004 8.00 ± 0.10	0.079 ± 0.002 2.00 ± 0.05	0.157 ± 0.004 4.00 ± 0.10	0.059-0/+0.004 1.5-0/+0.10	0.157 max 4.00 max	inches mm

Recommended Solder Pad for Wave Soldering

Type	0603	0805	1206	1210	Unit
Length (L)	0.063	0.079	0.126	0.126	inches
	1.60	2.00	3.20	3.20	mm
Width (W)	0.031	0.049	0.063	0.098	inches
	0.80	1.25	1.60	2.50	mm
a	0.031 ~ 0.039	0.039 ~ 0.055	0.071 ~ 0.098	0.071 ~ 0.098	inches
	0.80 ~ 1.00	1.00 ~ 1.40	1.80 ~ 2.50	1.80 ~ 2.50	mm
b	0.020 ~ 0.031	0.031 ~ 0.059	0.031 ~ 0.067	0.031 ~ 0.067	inches
	0.50 ~ 0.80	0.80 ~ 1.50	0.80 ~ 1.70	0.80 ~ 1.70	mm
c	0.024 ~ 0.031	0.035 ~ 0.047	0.047 ~ 0.063	0.071 ~ 0.098	inches
	0.60 ~ 0.80	0.90 ~ 1.20	1.20 ~ 1.60	1.80 ~ 2.50	mm



NOTE: Solder pad information is for reference only.

Recommended Solder Pad for Reflow Soldering

Type	0402	0603	0805	1206	1210	1812	Unit
Length (L)	0.043	0.063	0.079	0.126	0.126	0.177	inches
	1.10	1.60	2.00	3.20	3.20	4.50	mm
Width (W)	0.020	0.031	0.049	0.063	0.098	0.126	inches
	0.50	0.80	1.25	1.60	2.50	3.20	mm
a	0.018 ~ 0.022	0.024 ~ 0.031	0.031 ~ 0.047	0.071 ~ 0.098	0.071 ~ 0.098	0.098 ~ 0.138	inches
	0.45 ~ 0.55	0.60 ~ 0.80	0.80 ~ 1.20	1.80 ~ 2.50	1.80 ~ 2.50	2.50 ~ 3.50	mm
b	0.016 ~ 0.020	0.024 ~ 0.031	0.024 ~ 0.047	0.024 ~ 0.059	0.024 ~ 0.059	0.039 ~ 0.071	inches
	0.40 ~ 0.50	0.60 ~ 0.80	0.60 ~ 1.20	0.60 ~ 1.50	0.60 ~ 1.50	1.00 ~ 1.80	mm
c	0.018 ~ 0.022	0.024 ~ 0.031	0.035 ~ 0.063	0.047 ~ 0.079	0.071 ~ 0.126	0.091 ~ 0.138	inches
	0.45 ~ 0.55	0.60 ~ 0.80	0.90 ~ 1.60	1.20 ~ 2.00	1.80 ~ 3.20	2.30 ~ 3.50	mm

NOTE: Solder pad information is for reference only.

RoHS Compliance

Stackpole Electronics has joined the worldwide effort to reduce the amount of lead in electronic components and to meet the various regulatory requirements now prevalent, such as the European Union’s directive regarding “Restrictions on Hazardous Substances” (RoHS 3). As part of this ongoing program, we periodically update this document with the status regarding the availability of our compliant components. All our standard part numbers are compliant to EU Directive 2011/65/EU of the European Parliament as amended by Directive (EU) 2015/863/EU as regards the list of restricted substances.

RoHS Compliance Status						
Standard Product Series	Description	Package / Termination Type	Standard Series RoHS Compliant	Lead-Free Termination Composition	Lead-Free Mfg. Effective Date (Std Product Series)	Lead-Free Effective Date Code (YY/WW)
CML	Multilayer Ceramic Chip Capacitor	SMD	YES	100% Matte Sn over Ni	Always	Always

“Conflict Metals” Commitment

We at Stackpole Electronics, Inc. are joined with our industry in opposing the use of metals mined in the “conflict region” of the eastern Democratic Republic of the Congo (DRC) in our products. Recognizing that the supply chain for metals used in the electronics industry is very complex, we work closely with our own suppliers to verify to the extent possible that the materials and products we supply do not contain metals sourced from this conflict region. As such, we are in compliance with the requirements of Dodd-Frank Act regarding Conflict Minerals.

Compliance to “REACH”


We certify that all passive components supplied by Stackpole Electronics, Inc. are SVHC (Substances of Very High Concern) free and compliant with the requirements of EU Directive 1907/2006/EC, “The Registration, Evaluation, Authorization and Restriction of Chemicals”, otherwise referred to as REACH. Contact us for complete list of REACH Substance Candidate List.

Environmental Policy


It is the policy of Stackpole Electronics, Inc. to protect the environment in all localities in which we operate. We continually strive to improve our effect on the environment. We observe all applicable laws and regulations regarding the protection of our environment and all requests related to the environment to which we have agreed. We are committed to the prevention of all forms of pollution.

Features:

- 55°C to 125°C operating temperature range
- EIA sizes 0402, 0603, 0805, 1206, 1210 and 1812
- Capacitance offering from 100 pF to 47 uF
- RoHS compliant, REACH compliant, lead free and halogen free



Construction



- 1 - Ceramic layers (dielectric)
- 2 - Inner electrodes
- 3 - Base termination
- 4 - Nickel plating layer
- 5 - Tin plating layer

Electrical Specifications

Type/Code	Dielectric Code	Standard Tolerance		Capacitance Range					
		Code	Description	10V	16V	25V	50V	100V	
CML0402	X7R	K	± 10%	120 pF - 0.039 uF					-
				0.012 uF - 0.1 uF					-
CML0603	X7R	K	± 10%	150 pF - 0.1 uF					-
				0.012 uF - 0.18 uF					-
				0.12 uF - 0.33 uF					-
CML0805	X7R	K	± 10%	150 pF - 0.1 uF					-
				0.12 uF - 0.39 uF					-
				0.12 uF - 2.2 uF					-
CML1206	X7R	K	± 10%	150 pF - 1 uF					-
				2.2 uF - 4.7 uF					-
CML1210	X7R	K	± 10%	-					150 pF - 2.2 uF
				220 pF - 10 uF					-
				47 uF					-
CML1812	X7R	K	± 10%	-					270 pF - 1 uF
				470 pF - 4.7 uF					-
				6.8 uF					-

Note: J = 5% tolerance may be available


How to Order

C	M	L	0	4	0	2	X	7	R	1	0	3	K	T	5	0	V
Product Series		Size	Dielectric		Capacitance Range			Tolerance (*)		Packaging				Max Working Voltage			
Code	Description	Code	Code	0.1 pF to 0.10 uF (E12)		Code	Description	Code	Description	Size	Quantity						
CML	Multilayer Ceramic	0402 0603 0805 1206 1210 1812	X7R	EIA Code	Capacitance	J	± 5%	T	7" Paper Reel	Refer to Packaging Specifications				10V			
				101	100 pF	K	± 10%	7" Plastic Tape						16V			
				102	1000 pF										25V		
				103	0.01 uF										50V		
				104	0.1 uF										100V		
				105	1 uF												
				106	10 uF												

(*) Other tolerances may be available. Contact Stackpole.

Capacitance and Voltage Available																													
Dielectric		X7R																											
EIA Code	Size	0402				0603				0805				1206				1210				1812							
	VDCW	10V	16V	25V	50V	10V	16V	25V	50V	100V	10V	16V	25V	50V	100V	10V	16V	25V	50V	100V	10V	16V	25V	50V	100V	16V	25V	50V	100V
101	100 pF																												
121	120 pF																												
151	150 pF																												
181	180 pF																												
201	200 pF																												
221	220 pF																												
271	270 pF																												
331	330 pF																												
391	390 pF																												
471	470 pF																												
561	560 pF																												
681	680 pF																												
751	750 pF																												
821	820 pF																												
102	1000 pF																												
122	1200 pF																												
152	1500 pF																												
182	1800 pF																												
222	2200 pF																												
272	2700 pF																												
332	3300 pF																												
392	3900 pF																												
472	4700 pF																												
562	5600 pF																												
682	6800 pF																												
822	8200 pF																												
103	0.01 uF																												
123	0.012 uF																												
153	0.015 uF																												
183	0.018 uF																												
223	0.022 uF																												
273	0.027 uF																												
333	0.033 uF																												
393	0.039 uF																												
473	0.047 uF																												
563	0.056 uF																												
683	0.068 uF																												
823	0.082 uF																												
104	0.1 uF																												
124	0.12 uF																												
154	0.15 uF																												
184	0.18 uF																												
224	0.22 uF																												
274	0.27 uF																												
334	0.33 uF																												
394	0.39 uF																												
474	0.47 uF																												
564	0.56 uF																												
684	0.68 uF																												
824	0.82 uF																												
105	1 uF																												
125	1.2 uF																												
155	1.5 uF																												
225	2.2 uF																												
335	3.3 uF																												
475	4.7 uF																												
685	6.8 uF																												
106	10 uF																												
226	22 uF																												
476	47 uF																												

Mechanical Specifications and Packaging Specifications




Type/Code	Voltage	Capacitance Range	L	W	H	a	Unit	Packaging (7" Reel) Qty.	
								Paper Tape	Plastic Tape
CML0402X7R	10V - 50V	100 pF - 0.47 uF	0.039 ± 0.008 1.00 ± 0.20	0.020 ± 0.008 0.50 ± 0.20	0.020 ± 0.002 0.50 ± 0.05	0.010 ± 0.004 0.25 ± 0.10	inches mm	10000	-
CML0603X7R	10V - 100V	150 pF - 2.2 uF	0.063 ± 0.008 1.60 ± 0.20	0.031 ± 0.008 0.80 ± 0.20	0.031 ± 0.006 0.80 ± 0.15	0.016 ± 0.008 0.40 ± 0.20	inches mm	4000	-
CML0805X7R	10V	150 pF - 0.33 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.031 ± 0.004 0.80 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	4000	-
		0.47 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.031 ± 0.004 0.80 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	4000	-
		0.56 uF - 0.68 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.047 ± 0.004 1.20 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	3000
		0.82 uF - 1 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.039 ± 0.004 1.00 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	3000
		1.5 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.047 ± 0.004 1.20 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	3000
		2.2 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.031 ± 0.004 0.80 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	4000	-
	16V	150 pF - 0.33 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.031 ± 0.004 0.80 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	4000	-
		0.47 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.031 ± 0.004 0.80 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	4000	-
		0.56 uF - 0.68 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.047 ± 0.004 1.20 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	3000
		0.82 uF - 1 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.039 ± 0.004 1.00 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	3000
		1.5 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.047 ± 0.004 1.20 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	3000
		2.2 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.031 ± 0.004 0.80 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	4000	-
	25V	3.3 uF - 10 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.047 ± 0.004 1.20 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	2000
		150 pF - 0.33 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.031 ± 0.004 0.80 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	4000	-
		0.47 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.031 ± 0.004 0.80 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	4000	-
		0.56 uF - 0.68 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.047 ± 0.004 1.20 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	3000
		0.82 uF - 1 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.039 ± 0.004 1.00 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	3000
		1.5 uF - 2.2 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.047 ± 0.004 1.20 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	2000
3.3 uF - 4.7 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.047 ± 0.004 1.20 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	2000		

Mechanical Specifications and Packaging Specifications (cont.)

Type/Code	Voltage	Capacitance Range	L	W	H	a	Unit	Packaging (7" Reel) Qty.	
								Paper Tape	Plastic Tape
CML0805X7R	50V	150 pF - 0.33 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.031 ± 0.004 0.80 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	4000	-
		0.47 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.031 ± 0.004 0.80 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	4000	-
		0.56 uF - 0.68 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.047 ± 0.004 1.20 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	3000
		0.82 uF - 1 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.039 ± 0.004 1.00 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	3000
		1.5 uF - 2.2 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.047 ± 0.004 1.20 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	3000
	100V	100 pF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.028 ± 0.020 0.70 ± 0.50	0.020 ± 0.008 0.50 ± 0.20	inches mm	4000	-
		150 pF - 0.047 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.031 ± 0.004 0.80 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	4000	-
		0.056 uF - 0.1 uF	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.008 1.25 ± 0.20	0.047 ± 0.004 1.20 ± 0.10	0.020 ± 0.008 0.50 ± 0.20	inches mm	-	3000
	CML1206X7R	10V	200 pF - 0.33 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.031 ± 0.004 0.80 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	4000
0.47 uF - 0.68 uF			0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	3000
0.82 uF - 1.5 uF			0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.031 ± 0.004 0.80 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	4000	-
2.2 uF			0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
3.3 uF			0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	3000
4.7 uF - 22 uF			0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.063 ± 0.004 1.60 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
16V - 25V		200 pF - 0.33 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.031 ± 0.004 0.80 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	4000	-
		0.47 uF - 0.68 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	3000
		0.82 uF - 1.5 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.031 ± 0.004 0.80 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	4000	-
		2.2 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		3.3 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	3000
		4.7 uF - 10 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.063 ± 0.004 1.60 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
50V		200 pF - 0.33 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.031 ± 0.004 0.80 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	4000	-
		0.47 uF - 0.68 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	3000
		0.82 uF - 1.5 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.031 ± 0.004 0.80 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	4000	-
		2.2 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		3.3 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	3000
		4.7 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.063 ± 0.004 1.60 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
100V		150 pF - 0.056 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.031 ± 0.004 0.80 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	4000	-
		0.068 uF - 0.33 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	3000
		0.47 uF - 1 uF	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.012 1.60 ± 0.30	0.063 ± 0.004 1.60 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000

Mechanical Specifications and Packaging Specifications (cont.)


Type/Code	Voltage	Capacitance Range	L	W	H	a	Unit	Packaging (7" Reel) Qty.	
								Paper Tape	Plastic Tape
CML1210X7R	10V	220 pF - 0.47 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		0.68 uF - 1 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.063 ± 0.004 1.60 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		4.7 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		10 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.071 ± 0.004 1.80 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		47 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.098 ± 0.010 2.50 ± 0.25	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	500
	16V - 25V	220 pF - 0.47 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		0.68 uF - 1 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.063 ± 0.004 1.60 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		4.7 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		10 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.071 ± 0.004 1.80 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		22 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.098 ± 0.010 2.50 ± 0.25	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	500
	50V	220 pF - 0.47 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.047 ± 0.004 1.20 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		0.68 uF - 1 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.063 ± 0.004 1.60 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		4.7 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.071 ± 0.004 1.80 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		10 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.098 ± 0.010 2.50 ± 0.25	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	500
	100V	150 pF - 0.22 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.055 ± 0.004 1.40 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
		0.33 uF - 2.2 uF	0.126 ± 0.012 3.20 ± 0.30	0.098 ± 0.012 2.50 ± 0.30	0.063 ± 0.004 1.60 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	2000
CML1812X7R	16V - 25V	470 pF - 1 uF	0.177 ± 0.016 4.50 ± 0.40	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.004 1.60 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	1000
		1.5 uF - 6.8 uF	0.177 ± 0.016 4.50 ± 0.40	0.126 ± 0.012 3.20 ± 0.30	0.071 ± 0.004 1.80 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	1000
	50V	470 pF - 1 uF	0.177 ± 0.016 4.50 ± 0.40	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.004 1.60 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	1000
		1.5 uF - 4.7 uF	0.177 ± 0.016 4.50 ± 0.40	0.126 ± 0.012 3.20 ± 0.30	0.071 ± 0.004 1.80 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	1000
	100V	270 pF - 0.56 uF	0.177 ± 0.016 4.50 ± 0.40	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.004 1.60 ± 0.10	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	1000
		0.68 uF - 1 uF	0.177 ± 0.016 4.50 ± 0.40	0.126 ± 0.012 3.20 ± 0.30	0.063 ± 0.009 1.60 ± 0.24	0.024 ± 0.012 0.60 ± 0.30	inches mm	-	500

Environmental Characteristics										
Test	Test Specification					Test Condition				
Capacitance	Should be within the specified tolerance.					X7R: (Class II) Cap ≤ 10uF 1.0 ± 0.2 Vrms, 1 KHz ± 10% Cap > 10uF 0.5 ± 0.1 Vrms, 120 Hz ± 10%				
Dissipation Factor (DF)	X7R (Class II)	X7R (≥ 0402)	≥ 50V	25V	16V	10V				
			≤ 2.5%	≤ 3.5% (C < 0.47uF) ≤ 10.0% (C ≥ 0.47uF)	≤ 5% (C < 0.15uF) ≤ 10.0% (C ≥ 0.15 uF)					
Insulation Resistance	X7R (Class II)	C ≤ 25nF, Ri ≥ 10000M Ω C > 25nF, Ri*CR > 100S				Measuring Voltage: Rated Voltage (Max 500V) Duration: 60 ± 5 seconds Test Humidity: ≤ 75% Test Temperature: 25°C ± 5°C Test Current: ≤ 50 mA				
Dielectric Withstanding Voltage	No breakdown or damage.					Measuring voltage: Class II: 250% rated voltage Duration: 1 ~ 5 seconds Charge/Discharge Current: 50 mA max.				
Solderability	At least 95% of the terminal electrode is covered by new solder. Visual appearance: No visible damage.					Preheating Conditions: 80°C to 120°C, 10 ~ 30 seconds Solder Temperature: 235°C ± 5% (Sn/Pb: 63/37) Duration: 2 ± 0.5 seconds				
						Solder Temperature: 245°C ± 5°C (Lead-free) Duration: 2 ± 0.5 seconds				
Resistance to Soldering Heat	Item	X7R				Preheating Conditions: 100°C to 200°C; 10 ± 2 minutes Solder Temperature: 265°C ± 5°C Duration: 10 ± 1 seconds Clean the capacitor with solvent and examine it with a 10X (min.) microscope. Recovery Time: 24 ± 2 hours Recovery Condition: Room temperature.				
	Δ C/C	-5 ~ + 10%								
	DF	Same to initial value								
	IR	Same to initial value								
	Appearance: No visible damage. At least 95% of the terminal electrode is covered by new solder.									
Resistance to Flexure of Substrate (Bending Strength)	Appearance: No visible damage. Δ C/C: ≤ ± 10%					Test Board: Al2O3 or PCB Warp: 1 mm Speed: 0.5 mm / second The measurement should be made with the board in the bending position. Unit: mm 				
Termination Adhesion	No visible damage					Applied Force: 5 N Duration: 10 ± 1 seconds				
Temperature Cycle	X7R: Δ C/C: ≤ ± 10%					Preheating Conditions: up-category temperature 1 hour Recovery Time: 24 ± 1 hours Initial Measurement Cycling times: 5 times, 1 cycle, 4 steps:				
						Step	Temp. (°C)	Time (min.)		
						1	Low-category temp. X7R: -55°C	30 ± 3		
						2	Normal temp. (+20°C)	2 - 3		
						3	Up-category temp. X7R: +125°C	30 ± 3		
						4	Normal temp. (+20°C)	2 - 3		
Recovery time after test: 24 ± 2 hours										

Environmental Characteristics (cont.)


Test	Test Specification	Test Condition
Moisture Resistance	X7R: $\Delta C/C: \leq \pm 10\%$ DF: Not more than twice of initial value. IR: X7R: $R_i \geq 1000M \Omega$ or $R_i^*CR \geq 25S$ whichever is smaller Appearance: No visible damage	Temperature: $40^\circ C \pm 2^\circ C$ Humidity: 90 ~ 95% R.H. Duration: 500 hours Recovery Conditions: Room temperature Recovery Time: 48 hours (Class II)
Life Test	X7R: $\Delta C/C: \leq \pm 20\%$ DF: Not more than twice of initial value. IR: X7R: $R_i \geq 2000M \Omega$ or $R_i^*CR \geq 50 S$ whichever is smaller Appearance: No visible damage	Low-voltage ($< 100V$) Applied Voltage: 1.5 x rated voltage Duration: 1000 hours Temperature: $125^\circ C$ (X7R) Charge/Discharge Current: 50 mA max. Recovery Conditions: Room temperature Recovery Time: 48 hours (Class II)
Middle and High Voltage Life Test	X7R: $\Delta C/C: \leq \pm 20\%$ DF: Not more than twice of initial value. IR: X7R: $R_i \geq 2000M \Omega$ or $R_i^*CR \geq 50 S$ whichever is smaller Appearance: No visible damage	Applied voltage: $100V \leq$ rated voltage $< 500V$: 2 multiple $500V \leq$ rated voltage $\leq 1000V$: 1.5 multiple $> 1000V$ rated voltage: 1.2 multiple Duration: 1000 hours Charge/Discharge Current: 50 mA max. Temperature: $125^\circ C$ (X7R) Recovery Conditions: Room temperature Recovery Time: 48 hours (Class II)

Reel Specifications



Type/Code	A	B	C	D	E	F	G	Unit
CML_X7R (all sizes)	7.008 ± 0.079 178.00 ± 2.00	0.118 3.00	0.512 ± 0.020 13.00 ± 0.50	0.827 ± 0.031 21.00 ± 0.80	1.969 or more 50.00 or more	0.394 ± 0.059 10.00 ± 1.50	0.472 max 12.00 max	inches mm

Paper Tape Specifications




Type/Code	A0	B0	T	W	P0	Unit
CML0402X7R	0.026 ± 0.004 0.65 ± 0.10	0.045 ± 0.004 1.15 ± 0.10	0.031 below 0.80 below	0.315 ± 0.004 8.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	inches mm
CML0603X7R	0.043 ± 0.004 1.10 ± 0.10	0.075 ± 0.004 1.90 ± 0.10	0.043 max 1.10 max	0.315 ± 0.004 8.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	inches mm
CML0805X7R	0.057 ± 0.006 1.45 ± 0.15	0.091 ± 0.006 2.30 ± 0.15	0.043 max 1.10 max	0.315 ± 0.006 8.00 ± 0.15	0.157 ± 0.004 4.00 ± 0.10	inches mm
CML1206X7R	0.071 ± 0.008 1.80 ± 0.20	0.134 ± 0.008 3.40 ± 0.20	0.043 max 1.10 max	0.315 ± 0.008 8.00 ± 0.20	0.157 ± 0.004 4.00 ± 0.10	inches mm

Paper Tape Specifications (cont.)

Type/Code	P1	P2	D0	E	F	Unit
CML0402X7R	0.079 ± 0.002 2.00 ± 0.05	0.079 ± 0.002 2.00 ± 0.05	0.059-0/+0.004 1.5-0/+0.10	0.069 ± 0.002 1.75 ± 0.05	0.138 ± 0.002 3.50 ± 0.05	inches mm
CML0603X7R	0.079 ± 0.004 2.00 ± 0.10	0.157 ± 0.002 4.00 ± 0.05	0.059-0/+0.004 1.5-0/+0.10	0.069 ± 0.002 1.75 ± 0.05	0.138 ± 0.002 3.50 ± 0.05	inches mm
CML0805X7R	0.079 ± 0.004 2.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	0.059-0/+0.004 1.5-0/+0.10	0.069 ± 0.002 1.75 ± 0.05	0.138 ± 0.002 3.50 ± 0.05	inches mm
CML1206X7R	0.079 ± 0.004 2.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	0.059-0/+0.004 1.5-0/+0.10	0.069 ± 0.004 1.75 ± 0.10	0.138 ± 0.002 3.50 ± 0.05	inches mm

Plastic Tape Specifications




Type/Code	A	B	C	D	E	Unit
CML0805X7R	0.061 ± 0.008 1.55 ± 0.20	0.093 ± 0.008 2.35 ± 0.20	0.315 ± 0.008 8.00 ± 0.20	0.138 ± 0.002 3.50 ± 0.05	0.069 ± 0.004 1.75 ± 0.10	inches mm
CML1206X7R	0.077 ± 0.008 1.95 ± 0.20	0.142 ± 0.008 3.60 ± 0.20	0.315 ± 0.008 8.00 ± 0.20	0.138 ± 0.002 3.50 ± 0.05	0.069 ± 0.004 1.75 ± 0.10	inches mm
CML1210X7R	0.106 ± 0.004 2.70 ± 0.10	0.135 ± 0.004 3.42 ± 0.10	0.315 ± 0.004 8.00 ± 0.10	0.138 ± 0.002 3.50 ± 0.05	0.069 ± 0.004 1.75 ± 0.10	inches mm
CML1812X7R	0.144 ± 0.004 3.66 ± 0.10	0.195 ± 0.004 4.95 ± 0.10	0.472 ± 0.004 12.00 ± 0.10	0.217 ± 0.002 5.50 ± 0.05	0.069 ± 0.004 1.75 ± 0.10	inches mm

Type/Code	F	G	H	J	T	Unit
CML0805X7R	0.157 ± 0.004 4.00 ± 0.10	0.079 ± 0.004 2.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	0.059-0/+0.004 1.5-0/+0.10	0.059 max 1.50 max	inches mm
CML1206X7R	0.157 ± 0.004 4.00 ± 0.10	0.079 ± 0.004 2.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	0.059-0/+0.004 1.5-0/+0.10	0.073 max 1.85 max	inches mm
CML1210X7R	0.157 ± 0.004 4.00 ± 0.10	0.079 ± 0.002 2.00 ± 0.05	0.157 ± 0.004 4.00 ± 0.10	0.059-0/+0.004 1.5-0/+0.10	0.126 max 3.20 max	inches mm
CML1812X7R	0.315 ± 0.004 8.00 ± 0.10	0.079 ± 0.002 2.00 ± 0.05	0.157 ± 0.004 4.00 ± 0.10	0.059-0/+0.004 1.5-0/+0.10	0.157 max 4.00 max	inches mm

Recommended Solder Pad for Wave Soldering

Type	0603	0805	1206	1210	Unit
Length (L)	0.063	0.079	0.126	0.126	inches
	1.60	2.00	3.20	3.20	mm
Width (W)	0.031	0.049	0.063	0.098	inches
	0.80	1.25	1.60	2.50	mm
a	0.031 ~ 0.039	0.039 ~ 0.055	0.071 ~ 0.098	0.071 ~ 0.098	inches
	0.80 ~ 1.00	1.00 ~ 1.40	1.80 ~ 2.50	1.80 ~ 2.50	mm
b	0.020 ~ 0.031	0.031 ~ 0.059	0.031 ~ 0.067	0.031 ~ 0.067	inches
	0.50 ~ 0.80	0.80 ~ 1.50	0.80 ~ 1.70	0.80 ~ 1.70	mm
c	0.024 ~ 0.031	0.035 ~ 0.047	0.047 ~ 0.063	0.071 ~ 0.098	inches
	0.60 ~ 0.80	0.90 ~ 1.20	1.20 ~ 1.60	1.80 ~ 2.50	mm



NOTE: Solder pad information is for reference only.

Recommended Solder Pad for Reflow Soldering

Type	0402	0603	0805	1206	1210	1812	Unit
Length (L)	0.043	0.063	0.079	0.126	0.126	0.177	inches
	1.10	1.60	2.00	3.20	3.20	4.50	mm
Width (W)	0.020	0.031	0.049	0.063	0.098	0.126	inches
	0.50	0.80	1.25	1.60	2.50	3.20	mm
a	0.018 ~ 0.022	0.024 ~ 0.031	0.031 ~ 0.047	0.071 ~ 0.098	0.071 ~ 0.098	0.098 ~ 0.138	inches
	0.45 ~ 0.55	0.60 ~ 0.80	0.80 ~ 1.20	1.80 ~ 2.50	1.80 ~ 2.50	2.50 ~ 3.50	mm
b	0.016 ~ 0.020	0.024 ~ 0.031	0.024 ~ 0.047	0.024 ~ 0.059	0.024 ~ 0.059	0.039 ~ 0.071	inches
	0.40 ~ 0.50	0.60 ~ 0.80	0.60 ~ 1.20	0.60 ~ 1.50	0.60 ~ 1.50	1.00 ~ 1.80	mm
c	0.018 ~ 0.022	0.024 ~ 0.031	0.035 ~ 0.063	0.047 ~ 0.079	0.071 ~ 0.126	0.091 ~ 0.138	inches
	0.45 ~ 0.55	0.60 ~ 0.80	0.90 ~ 1.60	1.20 ~ 2.00	1.80 ~ 3.20	2.30 ~ 3.50	mm

NOTE: Solder pad information is for reference only.

RoHS Compliance

Stackpole Electronics has joined the worldwide effort to reduce the amount of lead in electronic components and to meet the various regulatory requirements now prevalent, such as the European Union’s directive regarding “Restrictions on Hazardous Substances” (RoHS 3). As part of this ongoing program, we periodically update this document with the status regarding the availability of our compliant components. All our standard part numbers are compliant to EU Directive 2011/65/EU of the European Parliament as amended by Directive (EU) 2015/863/EU as regards the list of restricted substances.

RoHS Compliance Status

Standard Product Series	Description	Package / Termination Type	Standard Series RoHS Compliant	Lead-Free Termination Composition	Lead-Free Mfg. Effective Date (Std Product Series)	Lead-Free Effective Date Code (YY/WW)
CML	Multilayer Ceramic Chip Capacitor	SMD	YES	100% Matte Sn over Ni	Always	Always

“Conflict Metals” Commitment

We at Stackpole Electronics, Inc. are joined with our industry in opposing the use of metals mined in the “conflict region” of the eastern Democratic Republic of the Congo (DRC) in our products. Recognizing that the supply chain for metals used in the electronics industry is very complex, we work closely with our own suppliers to verify to the extent possible that the materials and products we supply do not contain metals sourced from this conflict region. As such, we are in compliance with the requirements of Dodd-Frank Act regarding Conflict Minerals.

Compliance to “REACH”

We certify that all passive components supplied by Stackpole Electronics, Inc. are SVHC (Substances of Very High Concern) free and compliant with the requirements of EU Directive 1907/2006/EC, “The Registration, Evaluation, Authorization and Restriction of Chemicals”, otherwise referred to as REACH. Contact us for complete list of REACH Substance Candidate List.

Environmental Policy

It is the policy of Stackpole Electronics, Inc. to protect the environment in all localities in which we operate. We continually strive to improve our effect on the environment. We observe all applicable laws and regulations regarding the protection of our environment and all requests related to the environment to which we have agreed. We are committed to the prevention of all forms of pollution.